County Line Antique Tractor Club

Transfer Sled General Rules

Revised 1/29/2023

Transfer Sled General Rules:

- 1. Contestants enter at their own risk. County Line Antique Tractor Club will not be held responsible for any injuries, accidents or property damage. Judges reserve the right to stop any contestant operating in an unsafe or dangerous manner. Judges reserve discretion on all rules stated and not stated.
- 2. All tractor and operators must weigh in before the pull. Contestants must sign a waiver at the time of weigh in. Any contestant under the age of 18 must have a parent or guardian sign the waiver also. An adult responsible for the underage contestant must be at track side during the pull while minors are pulling. No one is allowed on the pulling track during the pull except the track workers.
- 3. Wheelie bars are required for 5mph and open class. They are recommended for the 3mph class. One hand must remain on the steering wheel at all times or both hands on a combination of the hand brake, hand clutch or throttle.
- 4. If the rear tire of the tractor touches the out of bounds line, the puller will be disqualified. If any weights or parts fall off the tractor, it will be disqualified.
- 5. No excessive RPM's.
- 6. Pullers in the 3, 5 & 8 mph classes cannot beep the horn after the speed cone.
- 7. Pullers may not protest another tractor after it leaves the track. Judges may check any tractor at any time.
- 8. No dual tires or chains. 4x4 tractors allowed but must have 4x4 disengaged while pulling.
- 9. Weights cannot extend more than 11' from the center of the rear axle forward, and cannot be behind the radius of the rear tire or 36" behind the center of the rear axle; whichever is further. Weights must not interfere with hooking and unhooking tractor.

3MPH Class Rules:

- 1. Speed limit is 3mph. No beeps allowed after speed cone.
- 2. Tire size is 15.5x 38 for 0-5000lbs. 18.4 for 33" and smaller rims. 5001 lbs and up is unlimited. Top cut tires only.
- 3. Hitches must be rigid in all directions and no more than 19" high. If a tractor does have wheelie bars then the hitch can be no closer than 18" from the center of the rear axle to the hook point. Hook must swing freely in the hook hole. Wheelie bars

must be behind the radius of the tire, able to support the weight of the tractor, pads must hit before hook and wheelie bars must be independent of the hitch.

If the tractor does not have wheelie bars, the hook point must be behind the radius of the tires at 19 inches.

5MPH Class Rules:

- 1. Speed limit is 5mph. No beeps allowed after the speed cone.
- 2. All tractors must have a working kill switch.
- 3. Hitch must be rigid in all directions, no higher than 19" and no less than 18" from the center of the axle to the hook point. Hook must swing freely in hook hole.
- 4. Tire size is unlimited. Full cut tires allowed.
- 5. Fenders and wheelie bars are required. Wheelie bars must be behind the tires and strong enough to support the weight of the tractor. Pads must hit before the hook does. Wheelie bars must be independent of the hitch.

8MPH Class Rules:

- 1. Speed limit is 8 mph. No beeps allowed after the speed cone.
- 2. All tractors must have a working kill switch.
- 3. Hitch must be rigid in all directions, no higher than 19" and no less than 18" from the center of the axle to the hook point. Hook must swing freely in hook hole.
- 4. Tire size is unlimited. Full cut tires allowed.
- 5. Fenders and wheelie bars are required. Wheelie bars must be behind the tires and strong enough to support the weight of the tractor. Pads must hit before the hook does. Wheelie bars must be independent of the hitch.

Open class rules:

- 1. No speed limit.
- 2. All tractors must have a working kill switch.
- 3. Hitch must be rigid in all directions, no higher than 19" and no less than 18" from the center of the axle to the hook point. Hook must swing freely in hook hole.
- 4. Tire size is unlimited. Full cut tires allowed.
- 5. Fenders and wheelie bars are required. Wheelie bars must be behind the tires and strong enough to support the weight of the tractor. Pads must hit before the hook does. Wheelie bars must be independent of the hitch.